

**CLY 265 010
KL70 CONDUCTOR CLAMP
Data Sheet**

Rubber Padding:

- Increases grip to prevent movement along conductor.
- Protects conductor

Material: DuPont® Zytel® ST801, a supertough PA66 Nylon.

- Environmentally responsible in production and reuse.
- Tough, light and surprisingly resilient in hot, chemically aggressive, humid, cold and wet environments.

Properties of Zytel® ST801 Nylon

Property	
Yield Stress	50 Mpa
Yield Strain	5.70%
Melting Temperature	263°C
Coefficient of Thermal Expansion	
Parallel (in flow direction)	$0.9 \times 10^{-4} \text{°C}$
Normal (perpendicular to flow)	$1.2 \times 10^{-4} \text{°C}$
Density	1080 kg/m ³
Oxygen Index	20%
Water Absorption, Equilibrium, 50% RH	
Equilibrium, 50% RH	2.20%
Saturation, immersed	6.70%
Rockwell Hardness	112

Data obtained from www.dupont.com and is subject to disclaimer found therein.



Gripper Hands: To enable easy jaw opening.

Mounting Fin: Easily adaptable

- 5mm diameter bushed hole or
- 2 x 3mm diameter pilot holes 40mm apart for tapping or adapting.

Conductor:

- Max diameter 70mm.
- Suitable for almost all overhead lines from LV to EHV

Spring Close Mechanism:

- Quick and easy installation and removal with use of special operating tool CLY E06 683 301.
- Strong springs securely fasten clamp to conductor indefinitely.



Clydesdale Ltd.

Instal House, 3 Sunbeam Road,
Woburn Road Ind. Est., Kempston,
Bedfordshire MK42 7BZ
United Kingdom

Tel: +44 (01234) 855855
Fax: +44 (01234) 855800
E-mail: sales@clydesdale.ltd.uk
www.clydesdale.ltd.uk
DS 265 010 REV 0 29/06/05 CB