

## Rubber Insulating Glove

**Ideal for use by Linesmen using Hot Glove techniques and other workers who come into contact with live or potentially live cables / circuits.**

**EN 60903 : 1993**



**The highest quality Rubber Insulating Glove ever produced, using the cement dipping process allowing for extra levels of comfort and dexterity as well as two colour identification.**

Class	Length	Part No.	Test Voltage AC	Working Voltage AC	Colour
0	14ö (355mm)	CLY 550 14**	5,000 V	1,000 V	Red / Yellow
1	14ö (355mm)	CLY 551 14**	10,000 V	7,500 V	Black
1	16ö (405mm)	CLY 551 16**	10,000 V	7,500 V	Black / Red
2	14ö (355mm)	CLY 552 14**	20,000 V	17,000 V	Yellow
2	16ö (405mm)	CLY 552 16**	20,000 V	17,000 V	Black / Yellow
3	16ö (405mm)	CLY 553 16**	30,000 V	26,500 V	Black / Yellow
3	18ö (455mm)	CLY 553 18**	30,000 V	26,500 V	Black / Yellow
4	16ö (355mm)	CLY 554 16**	40,000 V	36,000 V	Black / Yellow

<b>Colour</b>	Inside Colour is written first, Outer Colour is written second
<b>Sizing</b>	** Available in sizes 8 through 11 (enter size as suffix in part number)
<b>Categories passed</b>	R ó Acid, Oil and Ozone C ó Extreme Cold (-40°C) M ó Mechanical Strength
<b>Marking</b>	The glove is marked in accordance with EN 60903, stating mark of the independent CE approval body, size, manufacturer's name and month / year of manufacture. It is also marked with the CE logo and the double triangle image of the IEC. The glove is also marked in accordance with ASTM D120.
<b>Temperature</b>	Resistant to temperatures +55°C to -40°C
<b>Flame Retardancy</b>	Will self extinguish any flame
<b>Packaging</b>	Supplied as a pair contained within a plastic bag itself stores within a specifically designed cardboard box. Care instructions also enclosed.
<b>Storage</b>	Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of artificial heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 °C and 21 °C.

**Clydesdale Ltd.**

