

ABC, Copper, AAAC & ACSR Conductor Specifications

Technical Specification for Aerial Bundled Conductor (ABC) to ESI 43-13 Issue 2 : 1990

Nominal CSA of Conductor	No. of Cores	Nom. No. of Wires in Cores	Core \emptyset		Overall \emptyset	Weight	Calculated Breaking Load	Calculated DC Resistance @ 20°C	Min. Bending Radius of Bundle
			Min	Max					
mm	mm		mm	mm	mm		kN	Uohms/km	m
25	2	7	5.6	6.5	19.9	0.20	8.1	1200	159
35	2	7	6.6	7.5	21.9	0.26	11.3	868	175
50	2	19	7.7	8.5	24.7	0.35	15.3	641	198
70	2	19	9.3	10.2	28.1	0.48	22.1	443	225
95	2	19	11.0	12.0	32.7	0.65	30.6	320	262
25	4	7	5.6	6.5	23.8	0.40	16.3	1200	190
35	4	7	6.6	7.5	26.2	0.52	22.4	868	210
50	4	19	7.7	8.5	29.6	0.70	30.4	641	237
70	4	19	9.3	10.2	33.7	0.96	44.0	443	270
95	4	19	11.0	12.0	39.3	1.30	61.2	320	314
120	4	19	12.9	13.1	42.0	1.55	79.6	253	336

Clydesdale can take no responsibility under any circumstances, for any mistakes that may be contained within these tables. Please check facts with your own companies records before making decisions based on the above information.

Technical Specification for Hard Drawn Copper to BS 125

Nominal Area	Nominal Imperial Cu Equivalent	Stranding & Wire \emptyset	Overall \emptyset	Weight	Calculated Breaking Load
mm	in	/mm	mm	kg/km	kN
16	25	3/2.65	5.69	148.3	672.0
32	0.05	3/3.75	8.05	296.9	1296
70	0.1	7/3.55	10.65	621.0	2741
100	0.15	7/4.30	12.9	911.2	3838
125	0.2	19/2.90	14.5	1130	4929

Clydesdale can take no responsibility under any circumstances, for any mistakes that may be contained within these tables. Please check facts with your own companies records before making decisions based on the above information.

CLYDESDALE

Powering the Future

ABC, Copper, AAAC & ACSR Conductor Specifications

Technical Specification for All Aluminium Alloy Conductor (AAAC) to BS 3242:1970

Code Name	Nominal AI Area	Stranding & Wire Ø	Actual Area	Overall Ø	Weight	Calculated Breaking Load		Calculated DC Resistance @ 20°C	Length
	mm ²	/mm	mm ²	kg/km	m	kgt	kN	Uohms/km	km
-	0	7/1.47	11.88	4.41	32	340	3.33	2,771	10.63
Box	15	7/1.85	18.82	5.55	51	537	5.27	1,749	10.53
Acacia	20	7/2.08	23.79	6.24	65	680	6.67	1,384	10.46
Almond	25	7/2.34	30.10	7.02	82	861	8.44	1,093	10.5
Cedar	30	7/2.54	35.47	7.62	97	1014	9.94	0.9281	10.45
-	5	7/2.77	42.18	8.31	115	1205	11.82	0.7804	10.48
Fir	40	7/2.95	47.84	8.85	131	1367	13.41	0.6881	10.44
Hazel	50	7/3.30	59.87	9.90	164	1711	16.78	0.5498	10.43
Pine	60	7/3.61	71.65	10.83	196	2048	20.08	0.4594	10.45
-	0	7/3.91	84.05	11.73	230	2402	23.56	0.3917	10.44
Willow	75	7/4.04	89.73	12.12	245	2564	25.15	0.3669	10.47
-	0	7/4.19	96.52	12.57	264	2758	27.05	0.3411	10.45
-	0	7/4.45	108.9	13.35	298	3112	30.52	0.3023	10.44
Oak	100	7/4.65	118.9	13.95	325	3398	33.32	0.2769	10.46
-	100	19/2.82	118.7	14.10	326	3393	33.27	0.2787	10.41
Mulberry	125	19/3.18	150.9	15.90	415	4312	42.29	0.2192	10.39
Ash	150	19/3.48	180.7	17.40	497	5164	50.64	0.1831	10.39
Elm	175	19/3.76	211.0	18.80	580	6030	59.13	0.1568	10.4
Poplar	200	32/2.87	239.4	20.09	659	6841	67.09	0.1385	10.38
-	225	37/3.05	270.3	21.35	744	7724	75.75	0.1227	10.38
Sycamore	250	37/3.23	303.2	22.61	835	8664	84.97	0.1093	10.38
Upas	300	37/3.53	362.1	24.71	997	10350	101.5	0.09156	10.38
Walnut	350	37/3.81	421.8	26.67	1162	12053	118.2	0.07860	10.37
Yew	400	37/4.06	479.0	28.42	1319	13685	134.2	0.06921	10.38
Totara	425	37/4.14	498.1	28.98	1372	14233	139.6	0.06656	10.37
Rubus	500	61/3.50	586.9	31.50	1620	16771	164.5	0.05662	10.35
Araucaria	700	61/4.14	821.1	37.26	2266	23450	230.0	0.04047	10.35

Clydesdale can take no responsibility under any circumstances, for any mistakes that may be contained within these tables. Please check facts with your own companies records before making decisions based on the above information.

CLYDESDALE**Powering the Future****ABC, Copper, AAC & ACSR Conductor Specifications**

Technical Specification for Aluminium Conductor Steel Reinforced (ACSR) to BS 215 Part 2:1970

Code Name	Nominal Al Area mm ²	Stranding & Wire ϕ		Overall ϕ mm ²	Weight kg/km	Calculated Breaking Load		Calculated DC Resistance @ 20°C Uohms/km	Breakin g Length km
		Al /mm	Steel /mm			kgf	kN		
	mm ²	/mm	/mm	mm ²	kg/km	kgf	kN	Uohms/km	km
Mole	10	6/1.50	1/1.50	4.50	43.4	421	4.13	2,707	9.79
Squirrel	20	6/2.11	1/2.11	6.33	85.7	807	7.91	1,368	9.49
Gopher	25	6/2.36	1/2.36	7.08	106.9	979	9.60	1,093	9.24
Weasel	30	6/2.59	1/2.59	7.77	129.0	1167	11.44	0.9077	9.12
Fox	35	6/2.79	1/2.79	8.37	150.2	1342	13.16	0.7823	9.01
Ferret	40	6/3.00	1/3.00	9.00	172.4	1553	15.23	0.6766	9.08
Rabbit	50	6/3.35	1/3.35	10.05	215.7	1872	18.36	0.5426	8.75
Mink	60	6/3.66	1/3.66	10.98	257.1	2223	21.8	0.4545	8.72
Skunk	60		7/2.59	12.95	470.7	5396	52.92	0.4568	11.6
Beaver	70	6/3.99	1/3.99	11.97	305.5	2626	25.75	0.3825	8.67
Horse	70		7/2.79	13.95	545.8	6240	61.19	0.3936	11.6
Raccoon	75	6/4.10	1/4.10	12.30	322.6	2774	27.2	0.3622	8.67
Otter	80	6/4.22	1/4.22	12.66	341.8	2939	28.82	0.3419	8.67
Cat	90	6/4.50	1/4.50	13.50	389.2	3330	32.66	0.3007	8.63
Hare	100	6/4.72	1/4.72	14.16	428.5	3666	35.95	0.2733	8.63
Dog	100	6/4.72	7/1.57	14.15	396.5	3332	32.68	0.2733	8.46
Hyena	100	7/4.39	7/1.93	14.57	456.7	4183	41.02	0.2728	9.23
Cougar	125		1/3.05	15.25	428.3	3062	30.03	0.2190	7.31
Leopard	125	6/5.28	7/1.75	15.81	496.1	4156	40.76	0.2184	8.43
Tiger	125		7/2.36	16.52	620.0	5914	58.00	0.2203	9.81
Dingo	150		1/3.35	16.75	517.0	3642	35.72	0.1814	7.20
Wolf	150		7/2.59	18.13	746.0	7061	69.24	0.1828	9.73
Caracal	175		1/3.61	18.05	600.0	4191	41.10	0.1563	7.14
Lynx	175		7/2.79	19.53	865.0	8136	79.79	0.1576	9.66
Jaguar	200		1/3.86	19.30	686.0	4749	46.57	0.1367	7.08
Panther	200		7/3.00	21.00	1001	9407	92.25	0.1362	9.66
Lion	225		7/3.18	22.26	1125	10248	100.5	0.1213	9.36
Bear	250		7/3.35	23.45	1248	11339	111.2	0.1093	9.34
Goat	300		7/3.71	25.97	1530	13848	135.8	0.08911	9.30
Sheep	350		7/3.99	27.93	1771	15938	156.3	0.07704	9.25
Antelope	350		7/2.97	26.73	1467	12084	118.5	0.07727	8.55
Bison	350		7/3.00	27.00	1497	12328	120.9	0.07573	8.54
Deer	400		7/4.27	29.89	2027	18202	178.5	0.06727	9.23
Zebra	400		7/3.18	28.62	1683	13450	131.9	0.06740	8.29
Elk	450		7/4.50	31.50	2251	20221	198.3	0.06057	9.23
Camel	450		7/3.35	30.15	1849	14878	145.9	0.06073	9.25
Moose	500		7/3.53	31.77	2025	16417	161.00	0.0547	9.41

Clydesdale can take no responsibility under any circumstances, for any mistakes that may be contained within these tables. Please check facts with your own companies records before making decisions based on the above information.

Clydesdale Ltd, 3 Sunbeam Road, Woburn Road Industrial Estate, Kempston, Bedfordshire MK42 7BZ
Tel: 01234 855855 | Fax: 01234 855800 | Email: sales@clydesdale.net | Web: www.clydesdale.net