

CLY 280 GSC04
EARTHING CABLE KIT – GENERAL DETAILS
Data Sheet



The following items are the typical components used in the construction of a Clydesdale earthing cable kit.
All cable ends are terminated in shrouded copper ferrules.
Cable lengths and current handling will be matched to customer's specific requirements.



2136 - #2-665w copper earthing cable

- 127kg / 300m length
- Soft drawn #30AWG copper strands
- Jacket suitable for -45°C to +93°C
- 12.7mm O.D. Jacket
- Meets ASTM F855, Type I



4009 - 1.93m External Rod Clampstick.

- Tough thermoplastic head ferrule with 24mm opening.
- Heavy Rubber end cap
- ASTM F711
- 2.4kg Weight

1793 - Eye type, 1" duckbill clamp

- Smooth Jaw
- Strain relief
- Bronze body
- To suit main conductors from 4mm to 24mm
- ASTM F855, Class 4, Grade A
- 0.6kg weight



2093 Hanger stud

- Bronze construction
- 0.1kg weight



Clydesdale Ltd.

Wally Sample House, 3 Sunbeam Road,
Woburn Road Ind. Est., Kempston,
Bedfordshire MK42 7BZ
United Kingdom

Tel: +44 (01234) 855855
Fax: +44 (01234) 855800
E-mail: sales@clydesdale.net
www.clydesdale.net