

CLYDESDALE

Powering the Future

DATASHEET: CLY 55X Series

Cement Dipped Rubber Gloves



Ideal for use by Linesmen using Hot Glove techniques and other workers who come into contact with live or potentially live cables / circuits. The highest quality Rubber Insulating Glove ever produced, using the cement dipping process allowing for extra levels of comfort and dexterity as well as two colour identification.

Colour: Inside Colour is written first, Outer Colour second

Sizing: Available in sizes 8 through 11 (size = "xx" suffix on part number)

Simply measure the circumference of your hand in inches to give your glove size

Categories passed: R – Acid, Oil and Ozone C – Extreme Cold (-40°C)

Marking: The glove is tested and marked in accordance with EN 60903: It is also is marked with CE and the double triangle icon.

The glove is also marked in accordance with ASTM D120.

Temperature: Resistant to temperatures +55°C to -40°C

Flame Retardancy: Will self extinguish any flame

Packaging: Supplied as a pair contained within a plastic bag itself stores within a specifically designed cardboard box. Care instructions also enclosed.

Storage: Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of artificial heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 and 21 °C.

Arc Rating: Gloves are tested using a modified version of ASTM F1959 that has now been released as a new standard ASTM 2675. Phone us for more details if required.

Part Number	CLY 550 11xx	CLY 550 14xx	CLY 551 14xx	CLY 552 14xx	CLY 552 16xx	CLY 563 16xx	CLY 564 18xx
Voltage Class	0	0	1	2	2	3	4
Length	11" 279mm	14" / 355mm		16" / 406mm		18" 457mm	
Working Voltage	1000VAC	1000VAC	7500VAC	17000VAC	17000VAC	26500VAC	36000VAC
Test Voltage	5000VAC	5000VAC	10000VAC	20000VAC	20000VAC	30000VAC	40000VAC
Colour	Black	Red / Yellow	Black	Black	Yellow / Black	Yellow / Black	Yellow / Black
Cuff Style	Straight	Straight	Straight	Straight	Various	Bell	Bell
Arc Rating	25 cal/cm ² ATPV	Not tested	Not tested	93 cal/cm ² Ignition	Not tested	Not tested	Not tested