

# CLYDESDALE

Powering the Future

CLY 562 14-xx

Class 2, 14" Latex Insulating glove, Orange / Black



**CLY 562-14xx**

Ideal for use by electricians and other workers who come into contact with live or potentially live cables / circuits.  
Arguably the highest quality rubber-insulating glove ever produced, using a combination of traditional dip and cement dip technologies.

**Colour** Black inner and orange outer layer for clearer identification of damage to glove's surface during inspection.

**Sizing** "xx" Available in sizes 08 to 11 (add "xx" suffix into part number)

**Marking\*\*** The glove is marked in accordance with EN 60903, stating mark of the independent CE approval body, size, manufacturer's name and month / year of manufacture. It is also marked with the CE logo and the double triangle image of the IEC.

**Temperature** Resistant to temperatures +55°C to -40°C

**Flame Retardancy\*\*** As per requirements of EN 60903, will self extinguish any flame

**Packaging** Supplied as a pair contained within a white plastic bag bearing care instructions. Multiple Bags may be supplied in specifically designed cardboard box.

**Storage** Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity to sources of heat, light or ozone. It is desirable that the ambient temperature be between 10 °C and 21 °C.

Class	Length	Part No.	Test Voltage AC (rms)	Working Voltage AC (rms)	Colour
2**	14" (356mm)	CLY 562 16-2xx	20,000 V**	17,000 V**	Black Inner/ Orange Outer

\*\* All glove performance parameters and certification currently pending final type approval on this colour / construction.

DATA SHEET