

CLYDESDALE

Powering the Future

DATASHEET: CLY 561

Rubber Insulating Gloves, Class 1



Ideal for use by electricians and other workers who come into contact with live or potentially live cables / circuits.

Sizing:

Available in sizes 8 through 11 (size = "xx" suffix on part number)

Simply measure the circumference of your hand in inches to give your glove size

Categories passed:

A – Acid

Z – Ozone

C – Extreme Cold (-40°C)

M – Mechanical Strength – please be aware that under the latest version of EN 60903 : 2003 there is no specific category M, however this glove has been tested to and exceeds the requirements of the Category M requirement of EN 60903 : 1993.

Marking:

The glove is tested and marked in accordance with EN 60903, stating mark of the independent CE approval body, size, manufacturer's name and month / year of manufacture. It is also marked with the CE logo and the double triangle image of the IEC.

Temperature: Resistant to temperatures +55°C to -40°C

Flame Retardancy: As per requirements of EN 60903, will self extinguish any flame

Packaging: Supplied as a pair contained within a white bag bearing care instructions. Multiple bags may be supplied in specifically designed cardboard box,.

Storage: Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of artificial heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 and 21 °C.