

CLYDESDALE

Powering the Future

DATASHEET: CLY 650 14 XX

Composite Insulating Gloves

The composite chlorinated insulating glove is ideal for use by electricians and other workers who come into contact with live or potentially live cables / circuits.

A rubber-based glove with polychloroprene outer and Chlorinated inner to give an excellent combination of comfort and long life in demanding conditions.

Its anatomical shape makes flexing easier while ensuring a high level of protection.

There is no need to wear separate leather protectors with this category of mechanical insulating glove.

The glove is marked Voltage Class 0 (100V AC) in accordance with EN 60903:2003, stating mark of the the independent approval body, size, manufacturer's name and month / year of manufacture. It is also is marked with the CE logo and the double triangle icon.

Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of artificial heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 °C and 21 °C.



Standards:

EN 60903:2003

IEC 60903:2014

Category RC and mechanical

CE marked



LATEX ALLERGY TESTED

These sleeves and their matching gloves use a proprietary process for washing after initial dipping that removes latex protein to such a degree that the standardised latex protein test is not sensitive enough to register any remaining content. This has been further backed up by field testing among latex allergy sufferers with no reaction found.

Class	Length	Part No.
0	14" (360mm)	CLY 650 14**

****Available in sizes 8 through 11
(enter size as suffix in part number)**