

CLYDESDALE

POWERING THE FUTURE

DATASHEET: CLY 660 14XX

Composite Insulating Gloves

The composite insulating glove is ideal for use by electricians and other workers who come into contact with live or potentially live cables / circuits.

Employing a tougher, thicker version of the rubber found in our standard insulating gloves, these gloves give a combination of comfort and long life in demanding conditions without the need for leather overprotectors.

Their anatomical shape makes flexing easier while ensuring a high level of protection.

The glove is marked Voltage Class 0 (100V AC) in accordance with EN 60903 and IEC 60903 as well as featuring the CE logo, the double triangle icon, and the hammer icon for composite gloves.

This glove has also been arc tested at 100 cal/cm² in accordance with ASTM F2675:22

Gloves should be stored in their packaging. Care should be taken to ensure that gloves are not compressed, folded, or stored in proximity sources of artificial heat or exposed to sources of ozone. It is desirable that the ambient temperature be between 10 °C and 21 °C.

Standards:

- EN 60903:2003
- IEC 60903:2014
- Category RC and mechanical
- CE marked



LATEX ALLERGY TESTED

Class	Length	Part No.
0	14" (360mm)	CLY 660 14**

**Available in sizes 7 through 11
(enter size as suffix in part number)

These gloves use a proprietary process for washing after initial dipping that removes retained latex protein to such a degree that the standardised latex protein test is not sensitive enough to register any remaining content. This has been further backed up by field testing among latex allergy sufferers with no reaction found.