

CLYDESDALE

Powering the Future

DATASHEET: CLY 750 10400 Pole Mounted o/head Line Winch



A development from our previous pole mounted machines is our model 2060 winch. Reconductoring or coiling old conductor is a new concept in winch design. Built to comply with the latest CE regulations, it is constructed in manageable units, engine and gearbox, pole frame and drum holding frame. Capstan wheel and rope drum.

The drive unit has a built in self braking worm gear that retains the load when the drum is stopped, it has full forward and reverse gearing, because it has a capstan wheel operation it gives constant output thus giving better control over the operations.

The machine is designed to handle up to 157mm conductor with a length of 1000m however line conditions must be taken in to account.



Basic Equipment

- Engine with gearbox
- Pole and drum holding frame
- Capstan wheel
- Line spreader
- Exhaust hose
- Storage box
- (no drum included)

Technical Data

- Pulling force 400kp.
- Speed 0—30m/min
- Engine 4-stroke petrol 5.5hp
- Safety Auto brake retains load

Weight:

- Engine with gear and capstan 31kg
- Bracket 13kg
- Line spreader 3kg

A feature on the 2060 is the self aligning entry wheel. This ensures that the direction of pull is matched by the lay of the wheel ensuring easy flow of the rope. This arrangement even allows the rope to be used straight up the pole to which the machine is fitted.



Pilot rope drum excl rope
Art. No. 3060-0021



Split drum for coiling old conductor.

Art No. 2060-0010

Line spreader for split drum
Art. No. 2040-0220